

NuSpraylok Standard Flooring Adhesive Spray System

Superior Performance when Moisture Conditions Exist



**For Moisture
Conditions
up to
7 lbs. & 11pH**



A Revolutionary Adhesive System – Fast & Flexible

- Combats high moisture problems up to 7 lbs. and 11pH
- Applies standing up – reduces installation time up to 50%
- Releasable formula allows for easy removal later when sub floor access is required
- Install various flooring products on a variety of surfaces
- Environmentally friendly – CRI Green Label Plus certified

Get the Job Done – NuSpraylok Covers It All

Use with these floorcoverings:

- ECOFLEX Urethane Carpet Tile
- UltraSet Vinyl Carpet Tile
- VCT
- Luxury Vinyl
- Approved Broadloom

Adheres to these surfaces:

- Concrete
- Wood
- Existing VCT
- Fiberglass
- Metal
- Terrazzo

Product Benefits:

- Apply standing up, eliminates time on knees
- Reduces installation time up to 50%
- Reduces installer fatigue, increases productivity
- More than twice the coverage of bucket adhesives
- Eliminates the use of buckets and trowels
- Adheres to both porous and non-porous surfaces
- Floor may be used immediately after installing modular carpet or VCT
- Tile will not shift or peak
- Allows for sub floor access
- Low pressure system – no overspray

Additional Advantages:

- Self-contained system
- Easy cleanup
- Dries fast
- Long open time
- No waste
- Apply standing up
- Safer installations

Environmentally Friendly:

- No VOC's
- Water-based – no hazardous solvents
- Non-toxic
- Non-flammable
- Contains anti-microbial agents



Warranty: This product is warranted for 2 years. Warranty is against adhesive breakdown only. NuSpraylok will not prevent the buildup of alkalinity deposits (salts) or halt moisture flow on the sub floor. Deposits are not the result of using NuSpraylok adhesive, but from continuous high levels of vapor emissions being present. See full warranty for other conditions.

Flooring Adhesive Spray System

For Moisture Conditions up to 7 lbs. & 11pH

NuSpraylok Formula:

Floorcovering Type:

Carpet Tile - Vinyl (UltraSet)	DK115	<i>Approx. Coverage</i> <i>Installation Spray</i> <i>Dry Time</i> <i>Moisture</i> <i>pH</i>	4500 sf (500 sy) per cylinder Light to medium frost 15-30 Minutes 7 lbs. 11
Carpet Tile - Urethane (ECOFLEX)	DK127	<i>Approx. Coverage</i> <i>Installation Spray</i> <i>Dry Time</i> <i>Moisture</i> <i>pH</i>	2500 sf (277sy) per cylinder Medium to heavy frost 15-30 Minutes 7 lbs. 11
6' PVC Carpet	DK115	<i>Approx. Coverage</i> <i>Installation Spray</i> <i>Dry Time</i> <i>Moisture</i> <i>pH</i>	1800 sf (200 sy) per cylinder Medium to heavy frost 15-30 Minutes 7 lbs. 11
Approved Broadloom	DK127	<i>Approx. Coverage</i> <i>Installation Spray</i> <i>Dry Time</i> <i>Moisture</i> <i>pH</i>	100 sy per cylinder Heavy frost 15-30 Minutes 7 lbs. 11
VCT (Vinyl Composite Tile)	DK139	<i>Approx. Coverage</i> <i>Installation Spray</i> <i>Dry Time</i> <i>Moisture</i> <i>pH</i>	5000 sf (556 sy) per cylinder Light frost 15-30 Minutes 7 lbs. 11
Luxury Vinyl	DK115	<i>Approx. Coverage</i> <i>Installation Spray</i> <i>Dry Time</i> <i>Moisture</i> <i>pH</i>	4500 sf (500 sy) per cylinder Light to medium frost 15-30 Minutes 7 lbs. 11

Typical Properties:

Chemical Type:	SBR/Acrylic Blend
Appearance:	Milky White frost/clear
Odor:	Mild, non-chemical
Caution:	Aerosol, contents under pressure
Flash Point:	Will not burn
NFPA 704	
Flammability Rating:	0 (non-flammable)

General Information & Storage:

For safe handling and storage information, consult the Material Safety Data Sheet (MSDS).

See Mohawk's Installation Guidelines for specific instructions regarding installation applications.

Available Container Sizes:

28 lb pressurized cylinder 22 oz spray can

