

# Bigelow

# 3

## MOVING FORWARD

Made to Move - BQ219

Moving Ahead - BQ220

On the Rise - BQ221

Spectrum V 30 - BC246

QUICKSHIP



### Quickship Broadloom Service Parameters

- :: Up to 500 yards available for shipment in 3 business days
- :: 501 - 1000 yards ship within 7 business days





Made To Move



7194 On Target



7587 Think Smart



7698 In The Loop



7896 Go Getter



7973 Jump Start



7987 Just Focus



7989 Peak Awareness

PRODUCT SPECIFICATIONS

Style Name..... Made To Move  
 Product Type..... Broadloom  
 Construction ..... Tufted  
 Surface Appearance ..... Textured Patterned Loop  
 Nylon Type..... Colorstrand® SD Nylon  
 Gauge ..... 1/10 (39.37 rows per 10 cm)  
 Pile Weight ..... 20.0 oz. per sq. yd. (678 g/m<sup>2</sup>)  
 Pile Thickness..... .179" (4.55 mm)  
 Stitches Per Inch ..... 12.7 (50.00 per 10 cm)  
 Dye Method..... Solution Dyed  
 Protective Treatment..... Sentry Plus  
 Density ..... 4,022  
 Weight Density..... 80,440  
 Primary Backing..... Woven Polypropylene

Backing Foundation ..... Single Primary  
 Secondary Backing ..... Woven Polypropylene  
 Pattern Repeat ..... 4.0" (W) x 5.7" (L)  
 Width ..... 12' (3.66 m)  
 Flammability ..... ASTM E 648 Class 1 (Glue Down)  
 Smoke Density ..... ASTM E 662 Less Than 450  
 Static Propensity..... AATCC-134 Under 3.5 KV  
 IAQ Green Label ..... 14148216  
 IAQ Green Label Plus..... 8216  
 CRI Rating ..... Heavy Traffic  
 Warranties: Lifetime Limited Wear Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, Lifetime Static



Moving Ahead



7194 On Target



7587 Think Smart



7698 In The Loop



7896 Go Getter



7973 Jump Start



7987 Just Focus



7989 Peak Awareness

PRODUCT SPECIFICATIONS

Style Name..... Moving Ahead  
 Product Type..... Broadloom  
 Construction ..... Tufted  
 Surface Appearance ..... Textured Patterned Loop  
 Nylon Type..... Colorstrand® SD Nylon  
 Gauge ..... 1/10 (39.37 rows per 10 cm)  
 Pile Weight ..... 20.0 oz. per sq. yd. (678 g/m<sup>2</sup>)  
 Pile Thickness..... .171" (4.34 mm)  
 Stitches Per Inch ..... 13.0 (51.18 per 10 cm)  
 Dye Method..... Solution Dyed  
 Protective Treatment..... Sentry Plus  
 Density ..... 4,211  
 Weight Density..... 84,220  
 Primary Backing..... Woven Polypropylene

Backing Foundation ..... Single Primary  
 Secondary Backing ..... Woven Polypropylene  
 Pattern Repeat..... 4.0" (W) x 5.5" (L)  
 Width ..... 12' (3.66 m)  
 Flammability ..... ASTM E 648 Class 1 (Glue Down)  
 Smoke Density ..... ASTM E 662 Less Than 450  
 Static Propensity..... AATCC-134 Under 3.5 KV  
 IAQ Green Label ..... 14148216  
 IAQ Green Label Plus..... 8216  
 CRI Rating ..... Heavy Traffic  
 Warranties: Lifetime Limited Wear Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, Lifetime Static



On The Rise



7194 On Target



7587 Think Smart



7698 In The Loop



7868 Moving Up



7896 Go Getter



7916 Take Charge



7973 Jump Start



7987 Just Focus



7989 Peak Awareness

PRODUCT SPECIFICATIONS

Style Name..... On The Rise  
 Style Number..... BQ221  
 Collection Name..... Moving Forward  
 Product Type..... Broadloom  
 Construction..... Tufted  
 Surface Appearance..... Textured Patterned Loop  
 Nylon Type..... Colorstrand® SD Nylon  
 Gauge..... 1/10 (39.37 rows per 10 cm)  
 Pile Weight..... 20.0 oz. per sq. yd. (678 g/m<sup>2</sup>)  
 Pile Thickness..... .178" (4.52 mm)  
 Stitches Per Inch..... 12.8 (50.39 per 10 cm)  
 Dye Method..... Solution Dyed  
 Protective Treatment..... Sentry Plus  
 Density..... 4,045

Weight Density..... 80,900  
 Primary Backing..... Woven Polypropylene  
 Backing Foundation..... Single Primary  
 Secondary Backing..... Woven Polypropylene  
 Pattern Repeat..... 4.0" (W) x 7.8" (L)  
 Width..... 12' (3.66 m)  
 Flammability..... ASTM E 648 Class 1 (Glue Down)  
 Smoke Density..... ASTM E 662 Less Than 450  
 Static Propensity..... AATCC-134 Under 3.5 KV  
 IAQ Green Label..... 14148216  
 IAQ Green Label Plus..... 8216  
 CRI Rating..... Heavy Traffic  
 Warranties: Lifetime Limited Wear Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, Lifetime Static



Spectrum V 30



7234 Ebony Domino



7264 Olive Grove




7330 Only Natural



7450 Portabello Mix



7622 Navy Pier



7824 Java Latte



7876 Earth Scape



7945 Rushing River

PRODUCT SPECIFICATIONS

Style Name.....	Spectrum V 30	Backing Foundation .....	Single Primary
Product Type .....	Broadloom	Secondary Backing .....	Woven Polypropylene
Construction .....	Tufted	Pattern Repeat .....	None
Surface Appearance .....	Level Solid Cut	Width .....	12' (3.66 m)
Nylon Type .....	Fortis™ 6,6 Nylon	Flammability .....	ASTM E 648 Class 1 (Glue Down)
Gauge .....	1/10 (39.37 rows per 10 cm)	Smoke Density .....	ASTM E 662 Less than 450
Pile Weight .....	30.0 oz. per sq. yd. (1017 g/m <sup>2</sup> )	Static Propensity .....	AATCC-134 Under 3.5 KV
Pile Thickness.....	.220" (5.59 mm)	IAQ Green Label .....	14866678
Stitches Per Inch .....	10.3 (40.55 per 10 cm)	IAQ Green Label Plus.....	6678
Dye Method.....	Beck Dyed	CRI Rating.....	Moderate Traffic
Protective Treatment.....	Sentry	Warranties: Lifetime Limited Wear Warranty, Lifetime Static	
Density .....	4,909		
Weight Density.....	147,270		
Primary Backing .....	Woven Polypropylene		