



# MATERIAL SAFETY DATA SHEET

ACRYLIC PRESSURE SENSITIVE

Page: 2

=== SECTION VI - HEALTH HAZARD DATA HEALTH HAZARDS (ACUTE AND CHRONIC) CONTINUED ===

## INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Ingestion will cause discomfort and internal irritation. Stomach acids may coagulate the latex. Call a physician immediately.

If the product contains Ammonia, a loss of breath or fainting can occur if inhalation of Ammonia is sufficient.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None known specific to the product.

Individuals with sensitive airways (e.g., asthmatics) may react to airborne vapors.

## EMERGENCY AND FIRST AID PROCEDURES

EYES: Flush with water for at least 15 minutes. If irritation persists seek medical attention.

SKIN: Not a likely hazard, but if a rash develops seek medical attention. If product gets on the skin simply wash with soap and water.

INHALATION: Remove to fresh air. If breathing stops, then give artificial respiration and get medical attention.

INGESTION: If this occurs the stomach acid will coagulate the latex, seek medical attention for blockage.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: In case of a spill, apply saw dust or sweeping compound to soak up. For large spills use bailing methods into containers. Do not allow liquid to enter public sewers, water systems or surface water. CAUTION: Spilled liquid may be slippery. Use care to avoid falls.

WASTE DISPOSAL METHOD: For waste disposal purposes, a liquid with a pH between 2.0 and 12.5 is not defined or designated as hazardous by current provisions of the Federal (EPA) Resource Conservation and Recovery Act (RCRA, 40 CFR 261). Incinerate waste product when in liquid form in a properly permitted incineration facility in accordance with federal, state and local regulations. Liquids cannot be disposed of in a landfill. The product may be coagulated to separate the liquid from the polymer. The liquid portion may be discharged to an industrial or public treatment works with approval of appropriate permitting authorities. Solids can be sent to an approved landfill or preferably incinerated.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in a cool dry place away from oxidizing materials, use in a well ventilated area. Wash thoroughly after handling product.

OTHER PRECAUTIONS: Avoid contamination of skin. Remove and thoroughly launder contaminated clothing before reuse. Discard contaminated shoes.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION: If ventilation is inadequate, use respirators with Ammonia and organic vapor cartridges.

VENTILATION: Sufficient to keep any hazardous concentration below the TLV.

PROTECTIVE GLOVES: The use of rubber gloves is recommended when skin contact cannot be avoided.

EYE PROTECTION: Chemical resistant goggles or glasses should always be worn when dealing with this product or any other chemical.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Safety eye baths and showers should be nearby. For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact occurs, use protective clothing impervious to this material.

WORK/HYGIENIC PRACTICES: Handle all chemicals with caution and care. Always wash before eating, smoking or using toilet facilities. As with all chemicals, caution must be exercised through the prudent use of protective equipment and handling procedures to minimize exposure.

===== SECTION IX - DISCLAIMER =====

The data set forth in these sheets are based on information provided by the suppliers of the raw materials and chemicals used in the manufacture of the aforementioned product. Worthen Industries makes no warranty with respect to the accuracy of the information provided by their suppliers, and disclaims all liability of reliance thereon.